

ALPHA VE905

WORK WITH OCCASIONAL CHEMICAL RESISTANCE

Chemical glove ideal for handling mildly aggressive products



Specific benefits



Durability

· High-quality coating extends the life of the glove and provides excellent protection for the hand



Easy to use

· Chlorinated interior for easy glove donning



Performance

· Lightweight for optimal dexterity

Applications

- Public works
- Building
- Finishing works / Craftsmanship
- Manufacturing/Transformation
- Accomodation & Food services
- Maintenance

Certifications and norms





EN 388

0010X



EN ISO 374-1 TYPE C

TYPE C



EN ISO 374-5



EN 421:2010









ALPHA VE905

WORK WITH OCCASIONAL CHEMICAL RESISTANCE

Chemical glove ideal for handling mildly aggressive products

Standards - Details



EN388:2016+A1:2018

0 [0-4] ABRASION RESISTANCE 0 [0-5] CUT RESISTANCE 1 [0-4] TEAR RESISTANCE 0 [0-4] PIERCE RESISTANCE X [A-F] CUT RESISTANCE ISO 13997



EN 374

K I

Technical details

Glove kind	Tight glove
Glove family	Tight glove unsupported powder free
Tight glove kind	Unsupported
Inner finition	Powder free
Coating material and finition	Smooth latex
Coating level	Fully coated
Number of layer	Single layer
Thickness	0,40 mm
Arm level protection	Forearm cuff (< 400mm)
Benefits element	Reach, Vendor pack
Color	Natural
Size	6, 7, 8, 9, 10
Type of packaging	Sold individually





ALPHA VE905

WORK WITH OCCASIONAL CHEMICAL RESISTANCE

Chemical glove ideal for handling mildly aggressive products

Logistics information									
Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight	
VE905NA08	Natural	8/9	ALPHA VE905	3295249009724	13295249009721	144	12	10.7 kg	



