



Fall protection

# AM007

## ANCHORAGE DEVICES

Steel sling covered with a protective sheath, designed for structures with sharp angles



## Applications

- Agriculture
- Building
- Finishing works / Craftsmanship
- Maintenance
- Chemical industry
- Mining

## Certifications and norms



EN354

EN 795

TYPE B



Fall protection

# AM007

## ANCHORAGE DEVICES

Steel sling covered with a protective sheath, designed for structures with sharp angles

### Standards - Details

### Technical details

Type of equipment	Sling anchor
Composition of the main support	Steel
Length	1 m
Cable diameter	8 mm
Included elements	protective sheath
Color	Steel
SIZE	1 m
Ending	2 thimble ferrule loops
Lifespan from manufacturing	20 years
Weight	0,600 kg
Breaking Strength	12kN
Fall arrest work situations	Restraint, Rescue and evacuation, Long vertical movement or movement on inclined surface, Long vertical movement or movement on inclined surface for rope access work, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure, Short horizontal movement (less than 3 m)



Fall protection

# AM007

## ANCHORAGE DEVICES

Steel sling covered with a protective sheath, designed for structures with sharp angles

### Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
AM007	Steel	1 m	AM007	3660348006149	13660348006146	5	1	3.2 kg