



Fall protection

AN213100ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances



Specific benefits



Hygiene

- Harnesses and textiles can be washed with neutral soap



Performance

- Certification above the maximum rated load of 100 kg: product certified at 140 kg
- Strap with improved abrasion resistance and certified for use on sharp edges

Applications

- Public works
- Finishing works / Craftsmanship
- Automotive
- Power Energy
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG



Fall protection

AN213100ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances

Standards - Details

Technical details

Type of equipment	Energy absorber in lanyard webbing
Composition of the main support	Steel, Polyester
Length	1 m
With connector	yes
Color	Orange
Connector (user side)	Screw carabiner, steel, opening 18mm
Ending	2 sewn thimble loops
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing	10 years
Weight	1,3 kg
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection



Fall protection

AN213100ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
AN213100ZDD	Orange	1 m	AN213100ZDD	3295249265076	13295249265073	5	1	8.58 kg